

DOOR DEVICE FOR VENDING MACHINE

FIELD OF THE INVENTION

The invention relates to a door device for opening/closing the front of a vending machine body.

BACKGROUND OF THE INVENTION

FIG. 1 shows a conventional door body 100 of a vending machine. As shown in FIG. 1, the conventional door body 100 has a front 110, a side 120, and a top 130. The front 110 is provided with, for example, a display opening 111 for disposing therein a sample product display chamber (not shown) and a service opening 112 for disposing therein, for example, a money slot and a money amount indicator (not shown). Various functional parts are mounted on this door body 100 to constitute a door device for a vending machine.

The above-described conventional door body 100 is produced by molding as follows. A flat sheet metal member is provided. Openings, such as a display opening 111 and a service opening 112, are cut out, and the periphery of the member is then cut to a predetermined shape. The side 120 and the top 130 each are formed by bending by means of a bender. Next, the side 120 is connected by welding to the top 130 at a joint 140. Thereafter, the welded portion is polished for flattening. Finally, the welded portion is coated with a rust preventive to form a door body 100.

A separately assembled display chamber and the like are mounted on the molded door body 100 to produce a door device.

In the molding of the conventional door body 100, however, the step of bending, the step of welding, and the step of finishing are necessary. That is, the necessary number of steps is large, and, thus, this requires in a lot of time and causes a high cost in the molding. Further, although the welded portion is finished, finishing to a fully smooth extent is difficult. In this case, the welded portion having surface irregularities sometimes spoils the appearance of the door body. Further, the welded portion has poor corrosion resistance, and this necessitates, for example, rust preventing treatment after the finishing.

Further, since a large opening for assembling a display chamber and the like to the door body is provided, it is difficult to ensure the strength of the door device. In addition, since the display chamber and the like are separately assembled and mounted, the necessary number of steps for the production of the door body are large.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the invention to provide a door device for a vending machine which can be easily produced and has excellent appearance and strength.

According to the first feature of the invention, there is provided a door device for opening/closing the front of a vending machine body, said door device comprising an integrally molded structure of a front, a side, and a top of a door body, without any joint, produced by pressing of a single sheet of a metal member.

According to this construction, the front, the side, and the top of the door body are integrally molded by pressing without any joint. Therefore, unlike the prior art technique, welding for connecting the faces to each other is unnecessary. For this reason, the work is easy, and a door body possessing excellent appearance and corrosion resistance can be produced.

In the door device according to the first feature of the invention, preferably, a portion for connecting the front to the side, a portion for connecting the side to the top, and a portion for connecting the front to the top have a curved surface, while a portion for connecting three faces of the front, the side, and the top to one another has a spherical surface.

According to this construction, since the portion for connecting the front to the side, the portion for connecting the front to the top, and the portion for connecting the side to the top of the door body have a curved surface or a spherical surface. This can avoid local concentration of and can disperse the expansion and the contraction of the sheet member at the time of pressing and thus can prevent a local reduction in wall thickness of the door body or cockling.

Further, in the door device described just above according to the first feature of the invention, preferably, the curved surface of the portion for connecting the top to the side has been molded so that the radius of curvature is reduced toward the rear.

According to this construction, since the radius of curvature in the forward direction is large, the expansion and

the contraction of the sheet member at the time of pressing can be dispersed. At the same time, since the radius of curvature in the backward direction is small, even though the vending machine body in its corner portion, which, when the door device has been closed, faces the door device, is not formed at a large radius of curvature, there is no sense of incongruity in appearance.

In the above door devices according to the first feature of the invention, preferably, the bottom, the front, and the side of the door body have been integrally molded without any joint.

According to this construction, the bottom also is integrally formed without any joint. This more facilitates the production of the door device and, in addition, can improve the appearance and the corrosion resistance.

In the door device described just above according to the invention, preferably, a portion for connecting the front to the side, a portion for connecting the side to the bottom, and a portion for connecting the front to the bottom have a curved surface, while a portion for connecting three faces of the front, the side, and the bottom to one another has a spherical surface.

According to this construction, since the portion for connecting the front to the side, the portion for connecting the front to the bottom, and the portion for connecting the side to the bottom have a curved surface or a spherical surface. This can avoid local concentration of and can disperse the expansion and the contraction of the sheet member at the time

of pressing and thus can prevent a local reduction in wall thickness of the door body or cockling.

Further, in the door device described just above according to the first feature of the invention, preferably, the curved surface of the portion for connecting the bottom to the side has been molded so that the radius of curvature is reduced toward the rear.

According to this construction, since the radius of curvature in the forward direction is large, the expansion and the contraction of the sheet member at the time of pressing can be dispersed. At the same time, since the radius of curvature in the backward direction is small, even though the vending machine body in its corner portion, which, when the door device has been closed, faces the door device, is not formed at a large radius of curvature, there is no sense of incongruity in appearance.

Any one of the above door devices according to the first feature of the invention may have a decoration in a concave/convex form, on the front, produced by pressing.

According to this construction, the provision of a decoration in a concave/convex form on the front of the door body can realize the production of a door body possessing excellent appearance. The formation of the decoration by pressing enables the molding of the decoration simultaneously with the formation of the door body by pressing. This can reduce the production cost.

According to the second feature of the invention, there is provided a door device for opening/closing the front of a

vending machine body, said door device comprising an integrally molded structure of a front of the door body and a concave for displaying sample products or the like, produced by pressing of a single sheet of a metal member.

According to this construction, the front of the door body and the concave for displaying sample products or the like are integrally molded by pressing of a single sheet of a metal member. Therefore, the display chamber can be simply assembled. At the same time, the integrally molded display concave functions as a reinforcing member for the door body. Thus, a door device can be realized which has excellent rigidity.

This door device according to the second feature of the invention further comprises a display door that openably covers the display concave from the front and permits the interior of the display concave to be seen through the door.

According to this construction, the display door can prevent the entry of rainwater and the like into the display concave. Further, since the display door can be opened/closed from the front, this facilitates the replacement of sample products and the like displayed within the display concave.

The door device described just above according to the invention has a step which has been produced by pressing between the front and the display concave so that, when the display door has been closed, the step abuts against the rear of the display door and consequently functions as a margin for seal of the display door.

According to this construction, the step as a margin for

sealing of the display door is provided between the front and the display concave. This can reduce the level of a projection in the state of closing of the display door.

In the door device described just above according to the second feature of the invention, preferably, a soft sealing member is disposed on at least one of the rear of the display door and the step.

According to this construction, when the display door has been closed, the rear and the step of the display door are sealed by the seal member. This can more fully prevent the entry of rainwater and the like into the display concave.

Any one of the above door devices according to the second feature of the invention may have a decoration in a concave/convex form, on the inner face of the display concave, produced by pressing.

According to this construction, the provision of a decoration in a concave/convex form in the inner surface of the display concave can realize the production of a door body possessing excellent appearance. Further, the formation of the decoration by pressing enables the molding of the decoration simultaneously with the formation of the door body by pressing. This can reduce the production cost.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be explained in more detail in conjunction with the appended drawings, wherein:

FIG. 1 is a perspective view of a conventional door body.

FIG. 2 is a perspective view of a vending machine

provided with a door device according to the invention;

FIG. 3 is a perspective view of a vending machine in such a state that a display door is opened;

FIG. 4 is an enlarged view of the principal part of FIG. 2;

FIGS. 5A to 5C are diagrams showing the appearance of a door body, wherein FIG. 5A is a front view, FIG. 5B a side view, and FIG. 5C a plan view;

FIGS. 6A and 6B are longitudinal sectional views of the door body shown in FIG. 5A, wherein FIG. 6A is a sectional view taken on line A-A of FIG. 5A and FIG. 6B a sectional view taken on line B-B of FIG. 5A;

FIG. 7 is a cross-sectional view taken on line C-C of FIG. 5A showing the door body; and

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the invention will be explained in detail in conjunction with the accompanying drawings.

At the outset, the construction of a door device 1 will be explained in conjunction with FIGS. 2 and 3. Here FIG. 2 is a perspective view of a vending machine provided with the door device 1 according to the invention, and FIG. 3 a perspective view of a vending machine in such a state that a display door 11a is opened.

As shown in FIG. 2, the door device 1 of the invention comprises: a door body 3 the left end of which is pivotally supported through a hinge (not shown) onto the vending machine body 2; a display chamber provided in the door body 3; an

operation panel 5; a take-out port 11 provided at a lower part of the door body 3; and a repayment port 12.

The display chamber 4 comprises a display concave 35 of the door body 3 described below and a display door 4a which openably covers from the front the front face of the display concave 35. A plurality of sample products 4b are displayed within the display chamber 4. As shown in FIG. 3, this display door 4a has a panel 41a, formed of a transparent acrylic resin or the like, through which the interior of the display chamber 4 can be seen. The periphery of the display chamber 4 is surrounded by a sash 42a. The door body 4a in its right end is pivotally supported through a hinge (not shown) onto the door body 3 so that the display chamber 4 can be opened/closed from the front.

The panel 41a in the display door 4a has a plurality of selection buttons 43a for a user to select a desired product that are mounted at respective positions corresponding to sample products 4b. On the other hand, a seal member 44a formed of a soft material, such as a silicone, is provided in the inner surface of the sash 42a so as to surround the periphery of the sash 42a. Upon closing of the display door 4a, the seal member 44a is abutted against a step 37 of the door body 3, and consequently is sandwiched between the step 37 and the sash 42a to seal the display chamber 4. Therefore, in such a state that the display door 4a is closed, rainwater, dust or the like does not enter the display chamber 4. The seal member 44a may be disposed on the step 37 side.

A money amount indicator 5a, a money slot 5b, a latch 5c

for opening/closing the door device 1 and the like are provided on an operation panel 5 provided on a side of the display chamber 4.

The take-out port 11 is provided in the door body 3 for taking out a product carried out from the vending machine body 2, and an opening/closing door (not shown) is provided in the opening portion to prevent the entry of rainwater and the like into the take-out port.

The repayment port 12 is provided in the door body 3 in order to take out a change or the like. An opening/closing door is also provided in the opening portion of the repayment port 12 to prevent the entry of rainwater and the like.

Next, the door body 3 will be explained in conjunction with FIGS. 4 to 7. FIG. 4 is an enlarged view of the principal part of FIG. 2, FIG. 5 a diagram of the appearance of the door body 3, FIG. 6 a longitudinal sectional view of the door body 3, and FIG. 7 a cross-sectional view of the door body 3.

The door body 3 comprises a front 31, a side 32, a top 33, and a bottom 34 which, as shown in FIGS. 5 to 7, have been integrally molded without a joint by pressing a single sheet of a metal member.

All corner portions respectively for connection among the front 31, the side 32, the top 33, and the bottom 34 are formed in a curved form (see FIG. 2). An upper corner 300, where three faces of the front 31, the side 32, and the top 33 are connected to one another, and a lower corner 310, where three faces of the front 31, the side 32, and the bottom 34 are connected to one another, are formed in a spherical form.

As shown in FIG. 4, the corner 320 for connecting the top 33 to the side 32 is formed so that the radius of curvature of the front part A is 60 mm (R60) and the radius of curvature of the rear part B is 30 mm (R30). That is, the corner 320 is formed so that the radius of curvature is reduced toward the rear part. In the corner 320 formed in this way, since the radius of curvature in the front part is large, at the time of pressing, local concentration of expansion and contraction of the sheet member can be reduced, and the expansion and contraction force can be dispersed. At the same time, since the radius of curvature in the rear part is small, even though the vending machine body 2 in its corner 21, which, when the door device 1 has been closed, faces the door device, is not formed at a large radius of curvature, there is no sense of incongruity in appearance. Therefore, the shape of the vending machine body 2 in its corner 21, which has hitherto been formed at a right angle, is not required to be changed to a curved shape having a large radius of curvature. This can eliminate the need to significantly change the design of the vending machine body 2.

On the other hand, as with the corner 320, the corner 330 for connecting the bottom 34 to the side 32 is formed so that the radius of curvature of the front part is 60 mm (R60) and the radius of curvature of the rear part is 30 mm (R30). That is, the corner 330 is formed so that the radius of curvature is reduced toward the rear part. Therefore, the same function and effect as in the corner 320 can be provided.

As shown in FIGS. 5 to 7, a display concave 35 for

housing therein and displaying sample products 4b or the like is formed on the front 31 of the door body 3, and this display concave 35 also has been integrally molded with the door body 3 by pressing.

As shown in FIGS. 6A and 7, this display concave 35 has been molded so as to be concaved in a pot form in section. The side 350 of the display concave 35 is connected to the front 31 through the step 37 serving as a margin for seal of the display door 4a. On the other hand, the display concave 35 in its inner surface 351 has a mount face 351a for mounting, for example, a sample display base 4c (see FIG. 3) and a display face 351b which is provided at a lower part of the mount face 351a and displays an advertisement and the like. The disposition of a poster or the like on the display face 351b, of course, permits an advertisement of products through the display door 4a and the transparent panel 41a to consumers. Further, pressing of a decoration 7 formed of concaves and convexes on the display face 351b can realize an advertisement of products to consumers. For example, as shown in FIGS. 2 and 3, molding of a decoration 6 having a shape of a letter "DRINK" by means of press grooves can realize the provision of a door device 1 having a high level of appeal without disposing a poster and the like.

As shown in FIGS. 6A and 7, the step 37 as the margin for the seal of the display door 4a is provided at a position which is inward by one step corresponding to the thickness of the display door 4a from the front 31 of the door body 3. The step 37 is provided over the whole periphery of the display

2025 RELEASE UNDER E.O. 14176

door 4a. Therefore, when the display door 4a is closed, the display door 4a is not projected from the front 31 of the door body 3 and thus does not spoil the appearance of the vending machine body.

Further, as shown in FIGS. 6B and 7, an operation concave 36, which is slightly concaved backward, is provided on the front 31 of the door body 3 in its position corresponding to the operation panel 5 on which the money amount indicator 5a, the money slot 5b and the like are disposed. This operation concave 36 also has been integrally molded with the door body 3 by pressing. The provision of the operation concave 36 can distinguish the operation concave 36 from the other portion and thus can emphasize the position of the operation panel 5 (see FIG. 2) on which the money slot 5b and the like are disposed. Therefore, users can more easily operate the vending machine.

Further, a construction may also be adopted wherein a decoration 6 of concaves and convexes can be molded by pressing in a surplus space in the front 31 of the door body 3. For example, as shown in FIGS. 2 and 3, a decoration 6 having a shape of a beverage bottle may also be molded by means of a press groove. This can realize the provision of a door device 1 having a high level of appeal without print decoration and the like.

Next, the pressing of the door body 3 will be explained.

The door body 3 is formed from a single sheet of a flat metal member. At the outset, a flat sheet metal member, which has been cut into a predetermined shape, for example, by an NC

device, is provided, and a display concave 35, which requires the deepest drawing, is pressed by a female-male mold for first molding. Next, both the sides 32, the top 33, and the bottom 34 are pressed by a female-male mold for second molding. Finally, press molding, which simultaneously performs molding of the operation concave 36 to be shallowly drawn and finish shaping of details, is performed by a female-male mold for third molding. Thus, the molding of the door body 3 is completed.

In this case, the decoration 7 in the display concave 35 can be formed by pressing simultaneously with the molding of the display concave 35 (first molding). Further, the decoration 6 on the front 31 may be formed by pressing simultaneously with the finish molding (third molding).

According to this preferred embodiment, molding using the three molds for pressing can provide a door body 3 of a vending machine, comprising a deeply drawn portion, such as the display concave 35, shallowly drawn portions, such as decorations 6, 7, the highly curved side 32, and the top 33, that has even thickness and is free from wrinkles.

When the level of concaves and convexes in the drawn portion is low, molding using one or two molds for pressing is also possible. That is, three times of pressing are not limited to molding using three molds for pressing.

Further, instead of using the female-male mold, molding may be carried out, for example, by a hydroform single die molding method wherein only one of upper and lower dies is formed of a fixed material with the other die being formed of

a flexible material, such as rubber, and, in molding, even static pressure is externally applied. Pressing is not limited to this preferred embodiment.

Thus, since the door body 3 is molded by pressing using a single sheet of a flat sheet metal member, the faces are integrally molded without any joint. Therefore, unlike the prior art technique, this eliminates the need to perform welding for connecting the faces to each other and in its turn facilitates the work and can realize the production of a door device 1 having excellent appearance and corrosion resistance. Further, the decoration 7 on the display concave 35 and the decoration 6 on the front 31 can be molded simultaneously with other pressing process. This can reduce the cost of decoration in the door device 1. Further, since display concave 35 is integrally molded, the display chamber 4 can be easily assembled, and, in addition, the display concave 35 functions as a reinforcing member of the door body 3. This can enhance the rigidity of the door body. Further, even though the display door 4a has been broken for money or product robbery purposes, there is no possibility that the products and proceeds housed within the vending machine are easily robbed, because the display chamber 4 is covered with the display concave 35 which has been molded integrally with the front 31.

In the present preferred embodiment, the bottom 34 is integrally molded with the door body 3. Alternatively, as in the conventional door body 100 shown in FIG. 1, no bottom 34 may be provided.

The decorations 6, 7 may be in the form of concaves and

convexes that can be molded by pressing. That is, the decoration is not limited to the form of letters and beverage bottles referred to in the above preferred embodiment.

In FIGS. 2 to 4, the corners respectively for connection among the front 31, the side 32, the top 33, and the bottom 34, the upper corner 300 for connection of three faces of the front 31, the side 32, and the top 33, and the lower corner 310 for connection of three faces of the front 31, the side 32, and the bottom 34 are indicated by an auxiliary line for showing an image of a curved surface and a spherical surface. In fact, however, as shown in FIG. 5, this auxiliary line does not appear in the curved surface and the spherical surface.

As described above, according to the invention, since the door body is molded by pressing using a single sheet of a flat metal member, there is no joint in each face and the faces are integrally molded with each other. Therefore, unlike the prior art technique, welding for connecting the faces to each other is unnecessary. For this reason, the work is easy, and a door device possessing excellent appearance and corrosion resistance can be produced.

Further, the front of the door body and the concave for displaying sample products or the like are integrally molded by pressing of a single sheet of a metal member. Therefore, the display chamber can be easily assembled. At the same time, the integrally molded display concave functions as a reinforcing member for the door body. Thus, a door device can be realized which has excellent rigidity.

The invention has been described in detail with

particular reference to preferred embodiments, but it will be understood that variations and modifications can be effected within the scope of the invention as set forth in the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
223